



## SMD Connectors

### SMDflat 345/ 2 WS

terminal block, pin spacing: 4.00 mm, 2 pole, current rating: 6 A, voltage rating: 250 V, connection type: screwless



## Order Info

reference number (ref.no.)	351102
PU	1,500 (tape-on-reel)
EAN	4028012112456

## Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
connection type	screwless

## Technical Data

voltage rating	250 V
current rating	6 A
impulse voltage rating	4.0 kV
voltage rating according to UL	320 V
current rating according to UL	6 A
insulating material	PPA-GF
contact material	Spring Steel, Copper
core cross-section min.	0.2 mm <sup>2</sup>
core cross-section max.	0.75 mm <sup>2</sup>
core cross-section min. AWG	24
core cross-section max. AWG	18
flammability rating	V-0
max. ambient temperature operation	115 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	8.0-9.0 mm
pin spacing	4.00 mm
upper limit temperature	150 °C
ammonia resistance	yes

## Approvals

---

**acc. to EN 60947**

[Download PDF](#)

---

**acc. to UL**

[Download PDF](#)

---

## Accessories

---

**SMDflat 345 KU/ 2**

351152

---

**SMDflat WKZ**

351199

---