

Technical specification

CONNECTIONS	SDI Video Input	SD/HD/3G-SDI(75Ω)×4
	SDI Video Output	SD/HD/3G-SDI(75Ω)×2
	HDMI Video Output	HDMI type A×1
STANDARD	SDI Input Format Support	1080p 60/59.94/50/30/29.97/25/24/23.98 1080PsF 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 625i 50 PAL 525i 59.94 NTSC
	SDI & HDMI Output Format Support	1080p 60/50/30/25/24 1080i 60/50 720p 60/50/30/25
	SDI Video Rate	SD/HD/3G-SDI
	SDI Compliance	SMPTE 292M/SMPTE 259M/SMPTE 424M
	SDI & HDMI Color Space	YUV or RGB for inputs, YUV for outputs
	SDI Auto Switching	Auto selects SD, HD and 3G-SDI on input
CONTROLS	Dip Switches	Configuration
	LAN Port	Configuration and firmware updates
	USB Port	USB keyboard
SIZE	Dimension (LWD)	125.5 × 104 × 24.5mm
	Weight	465g
POWER	Power Connector	Threaded locking connector
	Power Consumption	6W
	Voltage Range	DC 6-24V
ENVIRONMENT	Operating Temperature	-20°C~60°C (HDMI output for 0°C~60°C)
	Storage Temperature	-30°C~70°C
	Relative Humidity	0%~90% non-condensing
WARRANTY	Warranty	3 year limited warranty